## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

| Supplier's name or trade mark: Näve Leuchten  Supplier's address: Technik, Austraße 5 74760 Forchtenberg Deutschland                 |                            |  |       |  |                           |  |  |  |
|--|----------------------------|--|-------|--|---------------------------|--|--|--|
|  |                            |  |       |  | Model identifier: 5311527 |  |  |  |
|  |                            |  |       |  | Type of light source:     |  |  |  |
| Lighting technology used:  | LED                        | Non-directional or directional:  | NDLS  |  |                           |  |  |  |
| Light source cap-type  | LED module                 |  |       |  |                           |  |  |  |
| (or other electric interface)  |                            |  |       |  |                           |  |  |  |
| Mains or non-mains:  | NMLS                       | Connected light source (CLS):  | No    |  |                           |  |  |  |
| Colour-tuneable light source:  | No                         | Envelope:  | -     |  |                           |  |  |  |
| High luminance light source:   | No                         |  |       |  |                           |  |  |  |
| Anti-glare shield:   | No                         | Dimmable:  | Yes   |  |                           |  |  |  |
| Product parameters   |                            |  |       |  |                           |  |  |  |
| Parameter  | Value                      | Parameter  | Value |  |                           |  |  |  |
| General product parameters:  |                            |  |       |  |                           |  |  |  |
| Energy consumption in on-<br>mode (kWh/1000 h), rounded<br>up to the nearest integer   | 1                          | Energy efficiency class  | Е     |  |                           |  |  |  |
| Useful luminous flux (φuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) | 143 in Wide<br>cone (120°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 2 900 |  |                           |  |  |  |
| On-mode power (P <sub>on</sub> ), expressed in W   | 1,1                        | Standby power (P <sub>sb</sub> ),<br>expressed in W and<br>rounded to the sec-<br>ond decimal  | -     |  |                           |  |  |  |
| Networked standby power (P <sub>net</sub> ) for CLS, expressed in W and rounded to the second decimal                                | -                          | Colour rendering in-<br>dex, rounded to the<br>nearest integer, or<br>the range of CRI-val-  | 81    |  |                           |  |  |  |

320

220

220

Outer dimen-

sions without

separate con-

trol gear, light-

control

ing

Height

Width

Depth

ues that can be set

tribution

Spectral power dis-

range 250 nm to 800

nm, at full-load

in

See image

in last page

| parts and non-<br>lighting con-<br>trol parts, if<br>any (millime-<br>tre) |   |                              |       |  |
|--|---|------------------------------|-------|--|
| Claim of equivalent power <sup>(a)</sup>                                   | - | If yes, equivalent power (W) | -     |  |
|  |   | Chromaticity coordi-         | 0,433 |  |
|  |   | nates (x and y)              | 0,391 |  |
| Parameters for LED and OLED light sources:                                 |   |                              |       |  |
| R9 colour rendering index value  | 3 | Survival factor              | -     |  |
| the lumen maintenance factor   | - |                              |       |  |

(a)'-': not applicable; (b)'-': not applicable;



